

optrel combi filter ABEP for swiss air

Technical data



Article number: 4088.450

Compatibility: swiss air
(ABEP-filter Cover – 4556.091 required for use)

Filter Type: TH3 A1B1E1 P R SL and TM3 A1B1E1 P R SL

A	Brown	Certain organic gases and vapors with boiling point >65°.
B	Grey	Certain inorganic gases and vapors (except carbon monoxide)
E	Yellow	Sulfur dioxide and other acid gases
P	white	Particles, dust, solid and liquid aerosols

(Protection classes according to EN 12941:1998/A2:2008 and EN12942/A2:2008)

Certification: EN 12941:1998/A2:2008 – TH3 A1B1E1 P R SL
EN 12942:1998/A2:2008 – TM3 A1B1E1 P R SL

Notified Body: 1024
Occupational Safety Research Institute
Jeruzalémská 1283
CZ-110 00 Praha 1
Czech Republic

Recommended air humidity range at workplace: < 90% Rh

Storage temperature: - 10 °C to + 55 °C humidity <90 % RH

Scope of delivery: combined filter, prefilter, manual

Packing: airtight, sealed trilaminate bag in cardboard outer packing

Country of origin: UK
Weight: 360g

Shelf Life: 7 years

Limitation for use Do not use where the oxygen level in the atmosphere is less than 17% or if there is an immediate danger to health or life (IDLH). Use in conjunction with optrel swiss air powered air purifying respirator, exclusively Filter capacity is reduced when used in wet (>80 % RH) and high temperature (>40°) environments.