

Technical Data

Part No. 4900.040 softhood, short version, black
4900.041 softhood, short version, grey
4900.042 softhood, short version, white



4900.050 softhood, long version, black
4900.051 softhood, long version, grey
4900.052 softhood, long version, white



Type description	PAPR hood to protect the respiratory tract and face from dust and aerosols
Colour	black, grey, white (depending on model)
Material	Visor: cellulose propionate Textile part: laminated polyethylene (PP+PE) Head harness: polypropylene
Operating temperature	0°C to + 60°C / 32°F to 140°F (with 20% - 95% Rh)
Storage temperature	-10°C to + 55°C / 14°F to 131°F (with 20% - 95% Rh)
Weight	Short version: 150g / 5.291oz Long version: 240g / 8.466oz
Dimension	Short version 280 mm / 210 mm / 270 mm Long version: 550 mm / 210 mm / 270 mm
Standards	EN12941 (TH3 in combination with e3000X) EN14594 (Class 3A in combination with supplied air) EN166
Marking	CE, UKCA
Application ranges	All work where increased protection of the head against dust and aerosols is necessary. Painting, sanding wood, plastic, or soft sandblasting (soft material, e.g. calcium carbonate, plastic granules or similar), medical field, cosmetics, laboratories, food production, waste disposal companies, mining, agriculture, automotive industry, construction industry, chemical industry, landfills, food industry, metal industry, agriculture, woodworking and many others.
Scope of delivery	softhood complete with instruction manual